NSN 5985-01-071-1767

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:

Body Surface Treatment:

Err-090

Any acceptable

Overall Length:



View Online at https://aerobasegroup.com/nsn/5985-01-071-1767

1.210 inches
Overall Diameter:
0.340 inches
Voltage Standing Wave Ratio:
1.35 and 1.60
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.4 gigahertz and +0.0/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.80/+0.80
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a

NSN 5985-01-071-1767

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000