# NSN 5985-01-072-9975

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-072-9975

### **Cross Sectional Shape:** Internal, rectangular external, rectangular **Thread Class:** 2b first flange single connection facility Thread Direction: Right-hand first flange single connection facility **Bend Angle In Deg:** 90.0 second bend h-plane **Tubing Wall Construction Style:** Seamless single tubing segment Flange Quantity: 2 Flange Inside Width: 1.312 inches second flange Flange Inside Height: 0.501 inches all flanges Flange Outside Width: 1.875 inches second flange Flange Outside Height: 1.875 inches second flange Flange Depth: 0.625 inches first flange Flange Connecting Hole Diameter: 0.172 inches second flange single connection facility **Voltage Standing Wave Ratio:** 1.16 **Insertion Loss In Decibels:** 0.20 Waveguide Outside Width: 1.250 inches **Thread Size:** 0.164 inches first flange single connection facility Waveguide Inside Width: 1.122 inches Waveguide Inside Height: 0.497 inches Waveguide Outside Height: 0.625 inches Flange Connecting Facility And Quantity: 4 unthreaded hole second flange single connection facility Flange Style: Cover type second flange

## NSN 5985-01-072-9975

Waveguide Assembly - Page 2 of 2



Waveguide Center To Center Distance:

3.780 inches

Waveguide Height:

0.400 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all flange

#### Surface Treatment:

Anodize all flange inside surfaces

Style Designator:

Double bend type

#### **Thread Series Designator:**

Unc first flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

Yes - demil/mli

Fiig:

A073a0