

View Online at <https://aerobasegroup.com/nsn/5985-01-074-4309>

Body Style:

Rectangular

Overall Length:

1.910 inches

Overall Height:

1.340 inches

Overall Width:

0.500 inches

Frequency Rating:

8.4 megahertz single frequency voltage standing wave ratio and 10.0 megahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.093 inches

Switch Type:

Nontransfer

Operating Temperature Range:

-40.0/+75.0 degrees celsius

End Application:

Test set, radar an/upm-145

Voltage Standing Wave Ratio:

1.25 single

Insertion Loss In Decibels:

0.12 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.17 dc

Actuator Voltage In Volts:

27.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

50.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Aluminum alloy body

Terminal Type And Quantity:

3 receptacle, coaxial

Specification Data:

97384-58139-90003 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0