NSN 5985-01-074-4625

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-074-4625 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** 1.570 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.25 and 1.30 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Mfm **Power Rating:** 1.0 watts average and 1.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 30.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+5.0 gigahertz and +5.0/+7.0 gigahertz **Connection Type Per Function:** Female output and male input **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 7.000 gigahertz **Fsc Application Data:** Radar antenna support sets and radomes, except specially designed Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5985-01-074-4625

Fixed Attenuator - Page 2 of 2



Fiig:

A20000