NSN 5985-01-075-8575

1b round, terminal/terminals in opposite surface

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:

Brass

Body Style:



View Online at https://aerobasegroup.com/nsn/5985-01-075-8575

, , , , , , , , , , , , , , , , , , , ,
Body Surface Treatment:
Silver plated, qq-s-365
Overall Length:
Between 2.110 inches and 2.230 inches
Overall Diameter:
0.600 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Tnc
Power Rating:
2.0 watts average and 3.0 kilowatts peak
Rf Signal Attenuation In Decibels:
15.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+2.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female output and male input
Mounting Method:
Terminal
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 2.000 gigahertz
Special Features:
3a1a13, ti 6820.2, fa 9996, vol 8, sec 8
Shelf Life:
N/a

NSN 5985-01-075-8575

Fixed Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000