NSN 5985-01-076-3966

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-076-3966

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange single connection facility

Thread Direction:

Right-hand second flange single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches first flange

Flange Inside Height:

0.628 inches first flange

Flange Outside Width:

1.875 inches first flange

Flange Outside Height:

1.875 inches first flange

Flange Inside Diameter:

1.125 inches first flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.169 inches first flange single connection facility

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.05

Waveguide Outside Width:

1.875 inches

Thread Size:

0.164 inches second flange single connection facility

Waveguide Inside Width:

1.253 inches

Waveguide Inside Height:

0.628 inches

Waveguide Outside Height:

1.875 inches

Waveguide Longer Offset Distance:

13.330 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

NSN 5985-01-076-3966 Waveguide Assembly - Page 2 of 2



Flange Style:
Choke type first flange
Waveguide Offset Distance:
4.120 inches
Flexibility:
Flexible single tubing segment
Material:
Any acceptable single tubing segment
Surface Treatment:
Any acceptable single tubing segment outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc second flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
Δ073a0