

View Online at <https://aerobasegroup.com/nsn/5985-01-076-5094>

Application Design:

Transmission line

Body Material:

Steel, stainless

Body Style:

1b round, terminal/terminals in opposite surface

Body Surface Treatment:

Passivated

Overall Length:

0.750 inches

Operating Temperature Range:

-55.0/+150.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 and 1.25 and 1.50 and 1.80

Coaxial Connector Series Designation:

Sma

Power Rating:

1.0 watts average

Rf Signal Attenuation In Decibels:

4.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.1/+12.0 gigahertz and +12.1/+15.0 gigahertz and +15.1/+18.0 gigahertz

Attenuation Accuracy In Decibels:

-0.10/+0.80

Mounting Method:

Connector

Terminal Type And Quantity:

3 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Precious Material And Location:

Terminal pins gold

Fsc Application Data:

Oscillator-isolator, countermeasures set

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000