NSN 5985-01-077-6475

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-077-6475

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
2.407 inches
Overall Width:
1.484 inches
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.250 inches
Shaft Length:
0.500 inches
Body Length:
1.906 inches
Schematic Diagram Designator:
Balanced "h" bridged
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Power Rating:
5.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.15
Overall Attenuation Range In Decibels:
+32.0/+65.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 bushing
Overall Attenuation Accuracy In Decibels:
-8.00/+8.00
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round, slotted
Impedance Rating In Ohms:
150.0 input-output
Test Data Document:

33875-ee-a0002 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

NSN 5985-01-077-6475

Variable Attenuator - Page 2 of 2



Terminal Type Aı	nd Quantity:
------------------	--------------

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0