

View Online at <https://aerobasegroup.com/nsn/5985-01-078-4013>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless third tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges and 1.253 inches all flanges

Flange Inside Height:

0.503 inches all flanges and 0.628 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.25

Insertion Loss In Decibels:

0.20

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Waveguide First Leg Length:

0.979 inches

Flange Style:

Cover type all flanges

Waveguide Second Leg Length:

2.000 inches

Waveguide Third Leg Length:

6.678 inches

Waveguide Fourth Leg Length:

4.969 inches

Flexibility:

Rigid third tubing segment

Material:

Copper alloy all flange

Style Designator:

Three bend type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0