## NSN 5985-01-078-4828

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-078-4828

## Application Design:

Transmission line

#### **Body Material:**

Aluminum

### Body Style:

Err-090

#### **Body Surface Treatment:**

Any acceptable

#### **Overall Length:**

2.720 inches

#### **Overall Diameter:**

1.650 inches

#### **Operating Tempurature Range:**

+0.0/+125.0 degrees celsius

#### Voltage Standing Wave Ratio:

### 1.15 and 1.20 and 1.25 and 1.40

Input Impedance Rating In Ohms:

```
50.0
```

#### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Ν

#### **Power Rating:**

10.0 watts average and 1.0 kilowatts peak

#### **Rf Signal Attenuation In Decibels:**

40.0

#### Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

#### Attenuation Accuracy Reference Frequency:

18.0 gigahertz

#### Attenuation Accuracy In Decibels:

-1.00/+1.00

#### Unpackaged Unit Weight:

4.000 ounces

#### **Mounting Method:**

Connector

#### **Terminal Type And Quantity:**

2 connector

#### Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

#### **Fsc Application Data:**

Antennas, waveguides and related equip.

# NSN 5985-01-078-4828

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000

