NSN 5985-01-078-6017

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-078-6017

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges and 1.006 inches all flanges

Flange Inside Height:

0.503 inches all flanges and 0.506 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.13

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Waveguide First Leg Length:

1.040 inches

Waveguide Fifth Leg Length:

1.040 inches

Flange Style:

Cover type all flanges

Waveguide Second Leg Length:

8.720 inches

NSN 5985-01-078-6017

Waveguide Assembly - Page 2 of 2



Waveguide Third Leg Length: 3.000 inches Waveguide Fourth Leg Length: 3.000 inches **Special Features:** 32.0 in. Microinch finish both flanges Flexibility: Flexible single tubing segment Material: Copper alloy all tubing segment and flange **Precious Material And Location:** All surfaces rhodium **Precious Material:** Rhodium **Surface Treatment:** Rubber single tubing segment outside surfaces Style Designator: Four bend type **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli

Fiig:

A073a0