NSN 5985-01-079-0447

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-079-0447

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.170 inches
Overall Height:
1.850 inches
Overall Width:
1.630 inches
Scale Linearity:
Linear
Scale Division Quantity:
90
Shaft Diameter:
0.250 inches
Shaft Length:
0.880 inches
Operating Tempurature Range:
-20.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 200.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unef
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.7
Overall Attenuation Range In Decibels:
+0.0/+90.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
9
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
1 threaded bushing
Fraguency Pange:

requeries range.

Between 0.000 gigahertz and 12.400 gigahertz

NSN 5985-01-079-0447 Variable Attenuator - Page 2 of 2



Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Segment Attenuation Range In Decibels:
+0.00/+50.00
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A223a0