NSN 5985-01-079-6117

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-079-6117

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches

Overall Height:

1.750 inches

Overall Width:

0.650 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Operating Tempurature Range:

+0.0/+60.0 degrees celsius

Voltage Standing Wave Ratio:

1.70

Coaxial Connector Series Designation:

Sma

Power Rating:

100.0 milliwatts peak

Overall Attenuation Range In Decibels:

+0.0/+3.5

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole

Frequency Range:

Between 11.000 gigahertz and 17.000 gigahertz

Adjustment Device Type And Quantity:

1 electronic, voltage controlled

Mounting Facility Pattern:

Two position diagonal

Impedance Rating In Ohms:

50.0 input-output

Special Features:

Voltage controlled

Terminal Type And Quantity:

3 connector, coaxial, male

NSN 5985-01-079-6117

Variable Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0

