NSN 5985-01-080-1414

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-080-1414

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.580 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.375 inches
Overall Height:
1.030 inches
Overall Width:
2.400 inches
Scale Linearity:
Nonlinear
Operating Tempurature Range:
-10.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Coaxial Connector Series Designation:
Sma
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.5/+3.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 1.000 gigahertz and 1.120 gigahertz
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Four position rectangular

0.112 inches

Mounting Facility Screw Thread Diameter:

NSN 5985-01-080-1414

Variable Attenuator - Page 2 of 2



50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0