NSN 5985-01-080-4553

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-080-4553

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.281 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.844 inches
Overall Height:
1.604 inches
Overall Width:
0.500 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
5.0 watts average and 3.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 12.000 gigahertz and 18.000 gigahertz
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:

1 shaft

NSN 5985-01-080-4553

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:

Four position rectangular

Shaft Type:

Round, slotted

Mounting Facility Screw Thread Diameter:

0.112 inches

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0