NSN 5985-01-083-4239

Fixed Attenuator - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5985-01-083-4239 |
|---|
| Application Design: |
| Transmission line |
| Body Material: |
| Steel, stainless |
| Body Style: |
| Err-090 |
| Body Surface Treatment: |
| Any acceptable |
| Overall Length: |
| 1.620 inches |
| Overall Diameter: |
| 0.375 inches |
| Operating Tempurature Range: |
| -65.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.15 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Sma |
| Power Rating: |
| 2.0 watts average |
| Rf Signal Attenuation In Decibels: |
| 31.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+4.0 gigahertz |
| Attenuation Accuracy Reference Frequency: |
| 4.0 gigahertz |
| Attenuation Accuracy In Decibels: |
| -1.00/+1.00 |
| Connection Type Per Function: |
| Female output and male input |
| Mounting Method: |
| Connector |

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 4.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-01-083-4239

Fixed Attenuator - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000