## **NSN 5985-01-083-4870** Fixed Attenuator - Page 1 of 2



| Fixed Attenuator - Page 1 of 2                               |
|--|
| View Online at https://aerobasegroup.com/nsn/5985-01-083-487 |
| Application Design:  |
| Transmission line  |
| Body Material:   |
| Steel, stainless   |
| Body Style:  |
| Err-090  |
| Body Surface Treatment:                                      |
| Any acceptable   |
| Overall Length:  |
| 1.210 inches   |
| Overall Diameter:  |
| 0.375 inches   |
| Operating Tempurature Range:                                 |
| -65.0/+125.0 degrees celsius                                 |
| Voltage Standing Wave Ratio:                                 |
| 1.15   |
| Input Impedance Rating In Ohms:                              |
| 50.0   |
| Output Impedance Rating In Ohms:                             |
| 50.0   |
| Coaxial Connector Series Designation:                        |
| Sma  |
| Power Rating:  |
| 2.0 watts average  |
| Rf Signal Attenuation In Decibels:                           |
| 5.0  |
| Voltage Standing Wave Ratio Frequency Range:                 |
| +0.0/+4.0 gigahertz  |
| Attenuation Accuracy Reference Frequency:                    |
| 4.0 gigahertz  |
| Attenuation Accuracy In Decibels:                            |
| -0.30/+0.30  |
| Connection Type Per Function:                                |
| Female input and male output                                 |
| Mounting Method:   |
| Connector  |
| Terminal Type And Quantity:                                  |
| 2 connector  |
| Frequency Range:   |
| Between 0.000 hertz and 4.000 gigahertz                      |
| Fsc Application Data:  |
| Antennas, waveguides, and related equipment                  |
|  |

## NSN 5985-01-083-4870

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000

