

View Online at <https://aerobasegroup.com/nsn/5985-01-084-7311>

Application Design:

Transmission line

Body Material:

Aluminum alloy

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.340 inches

Mounting Hole/stud Quantity:

4

Unthreaded Mounting Hole Diameter:

0.102 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.340 inches

Operating Temperature Range:

+25.0/+125.0 degrees celsius

End Application:

F-16 acft, fire control radar

Voltage Standing Wave Ratio:

1.07

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts peak

Rf Signal Attenuation In Decibels:

30.0

Attenuation Accuracy In Decibels:

-1.00/+1.00

Connection Type Per Function:

Female input and female output

Mounting Method:

Flange w/mounting hole

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 2.000 gigahertz and 12.400 gigahertz

Special Features:

Has bulkhead mounting flange

Fsc Application Data:

Aircraft gunnery fire control component

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000