## NSN 5985-01-085-1338

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-085-1338

view Online at https://aerobasegroup.com/nsn/3303-01-003-1330
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.450 inches
Overall Height:
1.910 inches
Overall Width:
1.500 inches
Distance Between Mounting Facility Centers:
1.125 inches
Operating Tempurature Range:
-54.0/+120.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Sma
Power Rating:
500.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
12
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 65.000 megahertz and 115.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.20/+0.20
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob

## NSN 5985-01-085-1338

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:

Two position in-line

Mounting Facility Screw Thread Diameter:

0.138 inches

Impedance Rating In Ohms:

50.0 input-output

## Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A223a0