NSN 5985-01-086-1203

Fixed Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-01-086-1203

Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated, qq-p-35
Overall Length:
1.150 inches
Overall Diameter:
0.320 inches
Operating Tempurature Range:
-54.0/+71.0 degrees celsius
End Application:
E-3a
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+7.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Temperature Sensitivity Attenuation In Decibels:
0.0001
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 gigahertz and 7.000 gigahertz
Shelf Life:
N/a

NSN 5985-01-086-1203

Fixed Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000