NSN 5985-01-087-4964

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-087-4964

| Application Design: |
|--|
| Transmission line |
| Body Material: |
| Aluminum alloy |
| Body Style: |
| 1b round, terminal/terminals in opposite surface |
| Overall Length: |
| 1.190 inches |
| Overall Diameter: |
| 0.380 inches |
| Operating Tempurature Range: |
| -54.0/+115.0 degrees celsius |
| End Application: |
| E-3a acft |
| Voltage Standing Wave Ratio: |
| 1.25 and 1.45 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Sma |
| Power Rating: |
| 2.0 watts peak |
| Rf Signal Attenuation In Decibels: |
| 2.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.30/+0.30 |
| Connection Type Per Function: |
| Female input and male output |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 12.400 gigahertz |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5985-01-087-4964

Fixed Attenuator - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A20000

