NSN 5985-01-088-0902

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-088-0902

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
1.900 inches
Overall Height:
0.887 inches
Overall Width:
0.700 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
0.325 inches
Operating Tempurature Range:
-0.0/+85.0 degrees celsius
Coaxial Connector Series Designation:
Sma
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.0
Overall Attenuation Range In Decibels:
+5.0/+70.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole
Frequency Range:
Between 9.600 gigahertz and 10.300 gigahertz
Overall Attenuation Accuracy In Decibels:
-3.00/+3.00
Adjustment Device Type And Quantity:
1 motor
Mounting Facility Pattern:
Two position in-line
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
3 connector, coaxial, female
Shelf Life:
N/a

NSN 5985-01-088-0902

Variable Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A223a0

