NSN 5985-01-088-6705

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-088-6705

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.500 inches
Overall Width:
1.875 inches
Distance Between Mounting Facility Centers:
1.125 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Bnc
Power Rating:
500.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.4
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
2 threaded stud
Frequency Range:
Between 0.000 gigahertz and 2.000 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Two position in-line
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
50.0 input-output

NSN 5985-01-088-6705

Variable Attenuator - Page 2 of 2



Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0