# NSN 5985-01-089-3509

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-089-3509

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

## Thread Class:

2b first flange all connection facilities

## **Thread Direction:**

Right-hand first flange all connection facilities

#### **End Application:**

Radar set, an/aps-94

#### Tubing Wall Construction Style:

Seamless single tubing segment

## Flange Quantity:

# 2

#### Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

#### Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

#### Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

#### Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

## Flange Inside Diameter:

1.406 inches first flange and 1.437 inches first flange

### Flange Depth:

0.423 inches second flange and 0.453 inches second flange

## Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

### Thready Qty Per Inch (tpi):

32 first flange all connection facilities

### Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

## Thread Size:

0.164 inches first flange all connection facilities

## Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

## Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

## Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

## Flange Style:

Cover type second flange

# NSN 5985-01-089-3509

Waveguide Assembly - Page 2 of 2



Waveguide Length:

4.840 inches

## Waveguide Center To Center Distance:

2.367 inches

Flexibility:

Flexible single tubing segment

## Material:

Rubber single tubing jacket

**Precious Material And Location:** 

Internal surfaces silver

**Precious Material:** 

Silver

## Surface Treatment:

Silver single tubing segment and flange inside surfaces

### Style Designator:

Offset bend type

### **Thread Series Designator:**

Unc first flange all connection facilities

## **Fsc Application Data:**

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

### Fiig:

A073a0