## NSN 5985-01-089-3594

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:

Brass



View Online at https://aerobasegroup.com/nsn/5985-01-089-3594

Body Style:
Err-090
Body Surface Treatment:
Tin plated
Overall Length:
1.500 inches
Overall Diameter:
0.550 inches
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+1.0 gigahertz
Attenuation Accuracy Reference Frequency:
1.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female input and female output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 1.000 gigahertz
Fsc Application Data:
Antennas, waveguies, and related equipment
Shelf Life:
N/a

## NSN 5985-01-089-3594

Fixed Attenuator - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A20000