NSN 5985-01-089-3594

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:

Brass



View Online at https://aerobasegroup.com/nsn/5985-01-089-3594

| Body Style: |
|--|
| Err-090 |
| Body Surface Treatment: |
| Tin plated |
| Overall Length: |
| 1.500 inches |
| Overall Diameter: |
| 0.550 inches |
| Voltage Standing Wave Ratio: |
| 1.20 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Sma |
| Power Rating: |
| 1.0 watts average |
| Rf Signal Attenuation In Decibels: |
| 3.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+1.0 gigahertz |
| Attenuation Accuracy Reference Frequency: |
| 1.0 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.50/+0.50 |
| Connection Type Per Function: |
| Female input and female output |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 1.000 gigahertz |
| Fsc Application Data: |
| Antennas, waveguies, and related equipment |
| Shelf Life: |
| N/a |

NSN 5985-01-089-3594

Fixed Attenuator - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A20000