NSN 5985-01-089-7225

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-089-7225

| Application Design: |
|---|
| Transmission line |
| Body Style: |
| Rectangular, terminal/terminals on opposite surfaces |
| Overall Length: |
| 3.180 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.500 inches |
| Overall Height: |
| 1.250 inches |
| Overall Width: |
| 1.500 inches |
| Mounting Hole/stud Quantity: |
| 4 |
| Operating Tempurature Range: |
| -40.0/+70.0 degrees celsius |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| N |
| Power Rating: |
| 20.0 watts average and 4000.0 watts peak |
| Rf Signal Attenuation In Decibels: |
| 10.0 |
| Attenuation Accuracy In Decibels: |
| -0.10/+0.10 |
| Mounting Method: |
| Threaded hole |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 962.000 megahertz and 1213.000 megahertz |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Yes - demil/mli

NSN 5985-01-089-7225

Fixed Attenuator - Page 2 of 2



Fiig:

A20000