NSN 5985-01-091-1405



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-091-1405 **Application Design:** Transmission line **Body Material:** Aluminum **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Body Surface Treatment:** Any acceptable **Overall Length:** 6.580 inches **Overall Height:** 3.060 inches **Overall Width:** 3.060 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.10 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 100.0 watts average and 10.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 30.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+1.0 gigahertz **Attenuation Accuracy Reference Frequency:** 1.5 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female input and female output **Unpackaged Unit Weight:** 2.500 pounds **Mounting Method: Terminal**

Terminal Type And Quantity:

2 connector

NSN 5985-01-091-1405

Fixed Attenuator - Page 2 of 2



Frequency	Range:
-----------	--------

Between 0.000 hertz and 1.500 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A20000