NSN 5985-01-091-5602

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-091-5602

| Application Design: |
|---|
| Transmission line |
| Body Style: |
| Coaxial type |
| Overall Length: |
| 2.870 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.340 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.840 inches |
| Overall Height: |
| 0.560 inches |
| Overall Width: |
| 2.760 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.370 inches |
| Operating Tempurature Range: |
| +0.0/+75.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.50 |
| Coaxial Connector Series Designation: |
| Sma |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Overall Attenuation Range In Decibels: |
| +17.0/+23.0 |
| Attenuation Accuracy Reference Frequency: |
| 4.0 gigahertz |
| Attenuation Variation Method: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 threaded hole |
| Frequency Range: |
| Between 2.000 gigahertz and 4.000 gigahertz |
| Overall Attenuation Accuracy In Decibels: |
| -3.00/+3.00 |
| Mounting Thread Quantity: |
| 40 per inch |
| Adjustment Device Type And Quantity: |

1 shaft

NSN 5985-01-091-5602

Variable Attenuator - Page 2 of 2



| Mounting Facility Pattern: |
|----------------------------|
|----------------------------|

Four position rectangular

Shaft Type:

Round, slotted

Mounting Facility Screw Thread Diameter:

0.112 inches

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0