NSN 5985-01-091-5603

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-091-5603

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.844 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.094 inches
Overall Height:
0.500 inches
Overall Width:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+17.0/+23.0
Attenuation Accuracy Reference Frequency:
8.0 gigahertz
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 4.000 gigahertz and 8.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-3.00/+3.00
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:

1 shaft

NSN 5985-01-091-5603

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Four position rectangular
Shaft Type:
Round, slotted
Mounting Facility Screw Thread Diameter:
0.112 inches
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0