NSN 5985-01-092-6434

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-092-6434

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.469 inches
Overall Height:
2.188 inches
Overall Width:
1.875 inches
Scale Linearity:
Linear
Scale Division Quantity:
110
Distance Between Mounting Facility Centers:
1.125 inches
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unf
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+110.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
110
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 gigahertz and 1.000 gigahertz
Mounting Thread Quantity:

32 per inch

NSN 5985-01-092-6434

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Two position in-line
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0