NSN 5985-01-092-6585

Fixed Attenuator - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5985-01-092-6585

View Online at https://aerobasegroup.com/nsn/5985-01-092-6585
Application Design:
Transmission line
Body Material:
Metal
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
1.240 inches
Overall Diameter:
0.385 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.30 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 200.0 watts peak
Rf Signal Attenuation In Decibels:
9.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.40/+0.40
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Test Data Document:
81349-mil-a-3933/16 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
apply approximated and parformance requirements and test conditions that are shown as "typical" "average" "", etc.)

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a

Shelf Life:

NSN 5985-01-092-6585

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A20000

