NSN 5985-01-092-6586

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-092-6586
Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
1b round, terminal/terminals in opposite surface
Overall Length:
1.240 inches
Overall Diameter:
0.390 inches
Operating Tempurature Range:
-65.0/+105.0 degrees celsius
Voltage Standing Wave Ratio:
1.45 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
500.0 milliwatts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-a-3933/16 government specification
Fsc Application Data:

N/a

Shelf Life:

Antennas, waveguides, and related equipment

NSN 5985-01-092-6586

Fixed Attenuator - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000