

View Online at <https://aerobasegroup.com/nsn/5985-01-092-9270>

Application Design:

Transmission line

Body Material:

Aluminum alloy

Body Style:

Irregular

Overall Length:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.820 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.950 inches

Overall Height:

0.750 inches

Overall Width:

2.000 inches

Unthreaded Mounting Hole Diameter:

Between 0.122 inches and 0.128 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

2.00

Coaxial Connector Series Designation:

Sma

Insertion Loss At Minimum Attenuation In Maximum Decibels:

3.5

Overall Attenuation Range In Decibels:

+0.0/+40.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 12.400 gigahertz and 18.200 gigahertz

Overall Attenuation Accuracy In Decibels:

-0.50/+0.50

Adjustment Device Type And Quantity:

1 electronic, voltage controlled

Mounting Facility Pattern:

Four position rectangular

Terminal Type And Quantity:

3 connector, coaxial, female and 3 pin

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0