NSN 5985-01-092-9509

Fixed Attenuator - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5985-01-092-9509

Application Design: Transmission line **Body Material:** Metal **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** 1.240 inches **Overall Diameter:** 0.385 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.30 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 200.0 watts peak **Rf Signal Attenuation In Decibels:** 6.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector **Frequency Range:** Between 0.000 hertz and 12.400 gigahertz **Test Data Document:**

81349-mil-a-3933/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349--3933/14-02 government specification

NSN 5985-01-092-9509

Fixed Attenuator - Page 2 of 2



Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A20000