## NSN 5985-01-093-8656

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-093-8656

View Online at	https://aerobasegroup.com/nsn/5985-01-093-8656
Application De	esign:
Transmission li	ine
Body Style:	
Coaxial type	
Overall Length	h:
3.660 inches	
Overall Height	t:
1.600 inches	
Overall Width:	:
2.070 inches	
Voltage Stand	ling Wave Ratio:
1.30	
Coaxial Conne	ector Series Designation:
Bnc	
Mounting Fac	ility Screw Thread Series Designator:
Unc	
Insertion Loss	s At Minimum Attenuation In Maximum Decibels:
0.5	
Overall Attenu	uation Range In Decibels:
+0.0/+10.0	
Attenuation V	ariation Method:
Stepped	
Step Position	Quantity:
10	
Attenuation P	er Step In Decibels:
1.0	
Mounting Fac	ility Type And Quantity:
2 threaded stud	d
Frequency Ra	nge:
Between 108.0	00 megahertz and 112.000 megahertz
Overall Attenu	ation Accuracy In Decibels:
-0.20/+0.20	
Mounting Thre	ead Quantity:
32 per inch	
Adjustment D	evice Type And Quantity:
1 knob	
Mounting Faci	ility Pattern:
Two position in	l-line
Mounting Fac	ility Screw Thread Diameter:
0.164 inches	
Impedance Ra	ating In Ohms:
50.0 input-outp	put

## NSN 5985-01-093-8656

Variable Attenuator - Page 2 of 2



## Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A223a0