NSN 5985-01-093-8656

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-093-8656

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.660 inches
Overall Height:
1.600 inches
Overall Width:
2.070 inches
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Bnc
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded stud
Frequency Range:
Between 108.000 megahertz and 112.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.20/+0.20
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Two position in-line
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:

50.0 input-output

NSN 5985-01-093-8656

Variable Attenuator - Page 2 of 2



Terminal Type A	and Quantity	/:
-----------------	--------------	-----------

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0