NSN 5985-01-093-8657

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-093-8657

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.570 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.600 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.600 inches
Overall Height:
2.952 inches
Overall Width:
1.000 inches
Operating Tempurature Range:
-54.0/+125.0 degrees celsius
Coaxial Connector Series Designation:
Sma
Power Rating:
5.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.7
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 7.000 gigahertz and 18.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-1.50/+1.50
Mounting Thread Quantity:
56 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:

0.112 inches

NSN 5985-01-093-8657

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms	lm	pedance	Rating	In	Ohms
--------------------------	----	---------	--------	----	-------------

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0