

View Online at <https://aerobasegroup.com/nsn/5985-01-093-9080>

Application Design:

Transmission line

Body Material:

Any acceptable

Body Style:

Rectangular terminal/terminals on three surfaces

Body Surface Treatment:

Gold plated

Overall Length:

0.647 inches

Overall Height:

0.035 inches

Overall Width:

0.372 inches

Voltage Standing Wave Ratio:

1.30

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Power Rating:

0.5 watts average and 100.0 watts peak

Rf Signal Attenuation In Decibels:

6.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+12.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Mounting Method:

Printed circuit

Terminal Type And Quantity:

3 tab, solder lug

Frequency Range:

Between 0.000 hertz and 12.000 gigahertz

Special Features:

Attenuator, chip rf

Precious Material And Location:

External surfaces gold

Precious Material:

Gold and platinum

Fsc Application Data:

Antennas, waveguides, and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000