NSN 5985-01-094-2993

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-094-2993 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** Between 1.150 inches and 1.350 inches **Overall Diameter:** 0.375 inches **Voltage Standing Wave Ratio:** 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma Rf Signal Attenuation In Decibels: 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+12.4 gigahertz **Attenuation Accuracy Reference Frequency:** 12.4 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz **Fsc Application Data:** Antennas, waveguides, and related equipment

Shelf Life: N/a

Unit Of Measure:

NSN 5985-01-094-2993

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000