

View Online at <https://aerobasegroup.com/nsn/5985-01-094-4445>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges

Flange Inside Height:

0.503 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.07

Insertion Loss In Decibels:

0.07

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

2.040 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Offset Distance:

2.040 inches

Special Features:

8.5 to 10.5 ghz; 600 w avg power and 60 kw peak

Flexibility:

Flexible single tubing segment

Material:

Copper alloy single tubing segment

Surface Treatment:

Rubber single tubing segment outside surfaces

Style Designator:

Bend type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0