NSN 5985-01-095-7489

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-095-7489

Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
8.280 inches
Overall Diameter:
0.827 inches
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
1.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
Voltage Standing Wave Ratio Frequency Range: +4.0/+10.0 gigahertz
+4.0/+10.0 gigahertz
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency:
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels:
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Connection Type Per Function:
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Connection Type Per Function: Female input and male output
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Connection Type Per Function: Female input and male output Mounting Method:
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Connection Type Per Function: Female input and male output Mounting Method: Connector
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity:
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 2.000 hertz and 18.000 gigahertz
+4.0/+10.0 gigahertz Attenuation Accuracy Reference Frequency: 4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Connection Type Per Function: Female input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 2.000 hertz and 18.000 gigahertz Fsc Application Data:

NSN 5985-01-095-7489

Fixed Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000