NSN 5985-01-096-8119

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-096-8119

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

End Application:

5840-01-046-7622, training set, electronic warfare, an/mst-t1

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.505 inches second flange

Flange Inside Height:

0.755 inches second flange

Flange Outside Diameter:

3.125 inches second flange

Flange Depth:

0.750 inches first flange

Flange Connecting Hole Diameter:

0.199 inches second flange single connection facility

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

1.500 inches

Thread Size:

0.190 inches first flange single connection facility

Waveguide Inside Width:

1.372 inches

Waveguide Inside Height:

0.622 inches

Waveguide Outside Height:

0.750 inches

Flange Connecting Facility And Quantity:

6 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Leg Length:

0.900 inches

Waveguide Longer Leg Length:

3.090 inches

NSN 5985-01-096-8119 Waveguide Assembly - Page 2 of 2



| Waveguide Center To Center Distance: |
|---|
| 4.390 inches |
| Waveguide Height: |
| 3.465 inches |
| Special Features: |
| E-plane bend; six connection facilities for each flange |
| Flexibility: |
| Rigid all tubing segment |
| Material: |
| Aluminum alloy all tubing segment and flange |
| Style Designator: |
| J-bend type |
| Thread Series Designator: |
| Unf first flange single connection facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . |
| Demilitarization: |
| Yes - demil/mli |
| Filg: |
| 4073a0 |
| |