## NSN 5985-01-096-8171

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-096-8171 **Application Design:** Transmission line **Body Material:** Steel, qq-s-763, class 302, 303, 304, 305, 310, or 316 **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** Between 2.180 inches and 2.300 inches **Overall Diameter:** 0.840 inches **Voltage Standing Wave Ratio:** 1.20 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 5.0 watts average and 1.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 8.0 **Attenuation Accuracy In Decibels:** -0.22/+0.22 **Temperature Sensitivity Attenuation In Decibels:** 0.0001 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 5.400 gigahertz and 5.900 gigahertz **Fsc Application Data:** Radar antenna support set and radomes, except specially designed Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5985-01-096-8171

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000