NSN 5985-01-096-8172

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-096-8172

Application Design:
Transmission line
Body Material:
Steel, qq-s-763, class 302, 303, 304, 305, 310, or 316
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
Between 2.180 inches and 2.300 inches
Overall Diameter:
0.840 inches
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
5.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
16.0
Attenuation Accuracy In Decibels:
-0.23/+0.23
Temperature Sensitivity Attenuation In Decibels:
0.0001
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 5.400 gigahertz and 5.900 gigahertz
Fsc Application Data:
Radar antenna support set and radomes, except specially designed
Shelf Life:
N/a
Unit Of Measure:

NSN 5985-01-096-8172

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000