NSN 5985-01-096-9897

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-096-9897

| Cross | Sect | ional | I Sha | no. |
|-----------|------|--------|--------|-----|
| U U O O O | JEUL | iviiai | ı Olla | DE. |

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Straight twist single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Height:

0.394 inches second flange

Flange Outside Width:

1.313 inches second flange

Flange Outside Height:

1.312 inches first flange

Flange Inside Diameter:

1.000 inches first flange

Flange Depth:

0.375 inches first flange

Flange Connecting Hole Diameter:

0.138 inches second flange all connection facilities and 0.144 inches second flange all connection facilities

Waveguide Outside Width:

0.702 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

0.622 inches

Waveguide Inside Height:

0.311 inches

Waveguide Outside Height:

0.391 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

5.000 inches

NSN 5985-01-096-9897 Waveguide Assembly - Page 2 of 2



| Flexibility: | | |
|--|--|--|
| Rigid single tubing segment | | |
| Material: | | |
| Copper alloy all tubing segment | | |
| Precious Material And Location: | | |
| External surfaces silver | | |
| Precious Material: | | |
| Silver | | |
| Surface Treatment: | | |
| Silver single tubing segment outside surface | | |
| Style Designator: | | |
| Straight type | | |
| Thread Series Designator: | | |
| Unc first flange all connection facilities | | |
| Shelf Life: | | |
| N/a | | |
| Unit Of Measure: | | |
| | | |
| Demilitarization: | | |
| No | | |
| Fiig: | | |
| A073a0 | | |
| | | |