# NSN 5985-01-097-0360

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-097-0360

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### **Thread Class:**

2b first flange single connection facility

#### **Thread Direction:**

Right-hand first flange single connection facility

#### Bend Angle In Deg:

90.0 single bend h-plane

#### **End Application:**

5840-01-046-7622, electronic warfare training set, an/mst-t1

#### Tubing Wall Construction Style:

Seamless all tubing segment

#### Flange Quantity:

2

Flange Inside Width:

0.706 inches second flange

#### Flange Inside Height:

0.395 inches second flange

#### Flange Outside Width:

1.313 inches second flange

#### Flange Outside Height:

1.312 inches first flange

#### Flange Inside Diameter:

1.000 inches first flange

#### Flange Depth:

0.375 inches first flange

#### Flange Connecting Hole Diameter:

0.144 inches second flange single connection facility

#### Maximum Operating Pressure:

20.0 pounds per square inch gage

#### Waveguide Outside Width:

0.702 inches

#### **Thread Size:**

0.138 inches first flange single connection facility

#### Waveguide Inside Width:

0.622 inches

#### Waveguide Inside Height:

0.311 inches

### Waveguide Outside Height:

0.391 inches

#### Waveguide Longer Offset Distance:

3.530 inches

# NSN 5985-01-097-0360

Waveguide Assembly - Page 2 of 2



## Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

### Flange Style:

Cover type second flange

# Waveguide Offset Distance:

1.400 inches

Flexibility:

Rigid all tubing segment

## Material:

Aluminum alloy 6061 all tubing segment and flange

## Style Designator:

Bend type

## Thread Series Designator:

Unc first flange single connection facility

## Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A073a0