NSN 5985-01-097-2319

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-097-2319

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 all bends e-plane

End Application:

5840-01-046-7622, electronic warfare training set, an/mst-t1

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange

Flange Inside Height:

0.628 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.625 inches first flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

NSN 5985-01-097-2319

Waveguide Assembly - Page 2 of 2



Flange Style: Cover type second flange Waveguide Center To Center Distance: 6.620 inches Waveguide Height: 2.000 inches **Special Features:** Bracket mtd on waveguide; 1 leg 2.502in lg Flexibility: Rigid all tubing segment Material: Aluminum alloy 6061 all tubing segment and flange Style Designator: Double bend type **Thread Series Designator:** Unc first flange single connection facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A073a0