NSN 5985-01-099-5955

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-099-5955

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.368 inches all flanges and 1.376 inches all flanges

Flange Inside Height:

0.618 inches all flanges and 0.626 inches all flanges

Flange Outside Diameter:

0.311 inches all flanges and 0.314 inches all flanges

Flange Depth:

0.735 inches all flanges and 0.765 inches all flanges

Voltage Standing Wave Ratio:

1.10

Maximum Operating Pressure:

10.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.496 inches and 1.504 inches

Thread Size:

0.190 inches all flanges all connection facilities

Waveguide Inside Width:

Between 1.368 inches and 1.376 inches

Waveguide Inside Height:

Between 0.618 inches and 0.626 inches

Waveguide Outside Height:

Between 0.746 inches and 0.754 inches

Flange Connecting Facility And Quantity:

6 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Length:

Between 107.980 inches and 108.020 inches

Flexibility:

Rigid single tubing segment

Surface Treatment:

Paint single tubing segment outside surfaces

NSN 5985-01-099-5955

Waveguide Assembly - Page 2 of 2



Style Designator:
Straight type
Thread Series Designator:
Unf all flanges all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0