NSN 5985-01-100-0769

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-100-0769 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Height:** 2.438 inches **Overall Width:** 1.438 inches **Scale Linearity:** Linear **Distance Between Mounting Facility Centers:** 2.438 inches **Voltage Standing Wave Ratio:** 1.20 and 1.50 **Coaxial Connector Series Designation:** Bnc **Power Rating:** 0.5 watts average **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.7 **Overall Attenuation Range In Decibels:** +0.0/+80.0 **Attenuation Variation Method:** Stepped **Step Position Quantity:** 80 **Attenuation Per Step In Decibels: Mounting Facility Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz **Overall Attenuation Accuracy In Decibels:** -0.50/+0.50 **Adjustment Device Type And Quantity:** 1 knob

Mounting Facility Pattern:

Two position in-line

Impedance Rating In Ohms:

50.0 output

Terminal Type And Quantity:

2 connector, coaxial, female

NSN 5985-01-100-0769

Variable Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0